


DECLARATION OF PERFORMANCE

as it has effect in the United Kingdom



1. Unique identification code of the product type:												
Stovax Stockton : Roomheater burning solid fuel without hot water supply												
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):												
Stockton 11 ECO WOOD FT - 2 DOOR : 721-243												
EN 13240:2001/A2:2004												
3. Intended use or uses of the construction product, in accordance with the applicable designated technical specification, as foreseen by the manufacturer:												
Roomheater burning solid fuel without hot water supply												
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):												
Stovax Limited Falcon Road Sowton Industrial Estate Exeter EX2 7LF United Kingdom Tel: +44(0)1392 474000 Email: info@stovax.com www.stovax.com												
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):												
N/A												
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:												
System 3 & 4												
7. In case of the declaration of performance concerning a construction product covered by a designated standard:												
The approved laboratory Kiwa - No. 0558 performed the determination of the product type on the basis of type testing under system 3 and issued test report 61256												
9. Declared performance:												
Haromised technical spefication					BS EN 13240:2001/A2:2004							
Essential characteristics					Performance							
Thermal output					Wood		Manufactured smokeless fuel					
Nominal heat output					11.3 kW		-- kW					
Room heating output					11.3 kW		-- kW					
Water heating output					-- kW		-- kW					
Energy efficiency					76.2 %		-- %					
Emission of combustion products					CO	PM	OGC	NO _x	CO	PM	OGC	NO _x
					(%)	(mg/Nm ³ @ 13% O ₂)			(%)	(mg/Nm ³ @ 13% O ₂)		
					0.11	12	62	92	--	--	--	--
Flue gas temperature at nominal heat output					318 °C		-- °C					
Surface temperature					Pass							
Electrical safety					Pass							
Cleanability					Pass							
Mechanical resistance (to carry a flue / chimney)					Pass							
Maximum operating pressure					-- bar							
Fire Safety												
Reaction to fire					A1							
Risk of burning fuel falling out					Pass							
Distance to combustible materials					Minimum distances							
					Side	500	mm					
					Rear	400	mm					
10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.												
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.												
Signed for and on behalf of the manufacturer by:												
 Ian Kingscott - Group Technical Director												
Exeter - 21 April 2020												